



1. Contact : Mechanical Contact
2. Rating : DC 12V, 50mA
3. Travel : 0.25 +0.2m/m - 0.1m/m
4. Contact Resistance : 100m Ω Max
5. Life : 100,000 Cycle Min
6. Package Quantity : 1,000pcs
7. L : 4.3, 5.0, 9.5, 7.0, 7.3, 8.5

Model No	TP1141	TP1141A
L	4.3	5.0
Stem Color	Black	Black



1. Contact : Mechanical Contact
2. Rating : DC 12V, 50mA
3. Travel : 0.25 +0.2m/m - 0.1m/m
4. Contact Resistance : 100m Ω Max
5. Life : 100,000 Cycle Min
6. Package Quantity : 700pcs



1. Contact : Mechanical Contact
2. Rating : DC 12V, 50mA
3. Travel : 0.25 +0.2m/m - 0.1m/m
4. Contact Resistance : 100m Ω Max
5. Life : 35,000 Cycle Min
6. Package Quantity : 1,500pcs
7. L : 4.3, 5.0

Model	L	Color
TP1146	4.3	Black
TP1147	5.0	White



1. Contact : Mechanical Contact
2. Rating : DC 12V, 50mA
3. Travel : 0.25 +0.2m/m -0.1m/m
4. Contact Resistance : 100m Ω Max
5. Life : 100,000 Cycle Min
6. Package Quantity : 700pcs
7. L : 4.3, 5.0

Model	Plating	Material	L
TP1144	Ag	NYLON66	4.3
TP1144 SNPB4	SN+Au	NYLON46	
TP1144 Au	Au	NYLON46	
TP1144A	Ag	NYLON66	5.0
TP1144A SNPB4	SN+Au	NYLON46	
TP1144 AuA	Au	NYLON46	



1. Contact : Mechanical Contact
2. Rating : DC 12V, 50mA
3. Travel : 0.25 +0.2m/m - 0.1m/m
4. Contact Resistance : 100m Ω Max
5. Life : 100,000 Cycle Min
6. Package Quantity : 700pcs
7. L : 4.3, 5.0

Model No	TP1144 WP	TP1144 WPA
L	4.3	5.0
Stem Color	White	Gray

Engineering Drawings are available for all parts