



multimec® 3F + 1X

Technical Data



- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
 - low temp: -40/+115°C
 - high temp: -40/+160°C





Dimensions (through-hole)





PCB layout





Dimensions (w/LED)





PCB layout (top view)



Dimensions (SMD)



PCB layout



How to order

3 F

Switch

□

Mounting

T through-hole
S surface mount

□ □

L 6 low temp.

H 9 high temp.

+

1 X

Cap



□ □

00 blue

02 green

03 grey

04 yellow

06 white

08 red

09 black

30 ultra blue

40 dusty blue

42 aqua blue

32 mint green

33 tele grey

34 melon

38 noble red

50 metal dark blue

53 metal light grey

57 metal dark grey

58 metal bordeaux

3 F

Switch

T

Mounting

T through-hole

□ □

L 6 low temp.

H 9 high temp.

+

□ □ □ □

LED

00 blue

20 green

40 yellow

60 white

80 red

2040 green/yellow

8020 red/green

8040 red/yellow

1 X

Cap



□ □

11 transparent

16 frosted white

Keycaps shown on this page can also be used on **illumec™ switch 4F**

Ordering example: 3FTL6 + 1X09 or 3FTL680 + 1X11